

§ 1915.97

(c) Employees shall not be permitted to work on the outboard side of lifeboats stowed on their chocks unless the boats are secured by gripes or otherwise secured to prevent them from swinging outboard.

§ 1915.97 Health and sanitation.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking, except where indicated otherwise.

(a) The employer shall provide all necessary controls, and the employees shall be protected by suitable personal protective equipment against the hazards identified in § 1915.1200 of this part and those hazards for which specific precautions are required in subparts B, C, and D of this part.

(b) The employer shall provide adequate washing facilities for employees engaged in the application of paints or coatings or in other operations where contaminants can, by ingestion or absorption, be detrimental to the health of the employees. The employer shall encourage good personal hygiene practices by informing the employees of the need for removing surface contaminants by thorough washing of hands and face prior to eating or smoking.

(c) The employer shall not permit employees to eat or smoke in areas undergoing surface preparation or preservation or where shipbreaking operations produce atmospheric contaminants.

(d) The employer shall not permit employees engaged in ship repair work on a vessel to work in the immediate vicinity of uncovered garbage and shall ensure that employees working beneath or on the outboard side of a vessel are not subject to contamination by drainage or waste from overboard discharges.

(e) No minor under 18 years of age shall be employed in shipbreaking or related employments.

[52 FR 31886, Aug. 24, 1987, as amended at 67 FR 44543, July 3, 2002]

§ 1915.98 First aid.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking.

(a) Unless a first aid room and a qualified attendant are close at hand

29 CFR Ch. XVII (7–1–11 Edition)

and prepared to render first aid to employees on behalf of the employer, the employer shall furnish a first aid kit for each vessel on which work is being performed, except that when work is being performed on more than one small vessel at one pier, only one kit shall be required. The kit, when required, shall be kept close to the vessel and at least one employee, close at hand, shall be qualified to administer first aid to the injured.

(b) The first aid kit shall consist of a weatherproof container with individual sealed packages for each type of item. The contents of such kit shall contain a sufficient quantity of at least the following types of items:

Gauze roller bandages, 1 inch and 2 inch.
Gauze compress bandages, 4 inch.
Adhesive bandages, 1 inch.
Triangular bandage, 40 inch.
Ammonia inhalants and ampules.
Antiseptic applicators or swabs.
Burn dressing.
Eye dressing.
Wire or thin board splints.
Forceps and tourniquet.

(c) The contents of the first aid kit shall be checked before being sent out on each job and at least weekly on each job to ensure that the expended items are replaced.

(d) There shall be available for each vessel on which ten (10) or more employees are working one Stokes basket stretcher, or equivalent, permanently equipped with bridles for attaching to the hoisting gear, except that no more than two stretchers are required on each job location. A blanket or other liner suitable for transferring the patient to and from the stretcher shall be provided. Stretchers shall be kept close to the vessels. This paragraph does not apply where ambulance services which are available are known to carry such stretchers.

§ 1915.100 Retention of DOT markings, placards and labels.

(a) Any employer who receives a package of hazardous material which is required to be marked, labeled or placarded in accordance with the U. S. Department of Transportation's Hazardous Materials Regulations (49 CFR parts 171 through 180) shall retain those markings, labels and placards on the